

AIR NIPPER



Specifications	BODY				Recommended Air Pressure 90 psi (6.3 kg/cm ²)					
	Model	Size (mm)	Net Weight (kgs)	Standard Blade Wire	Plastic	Air Pressure (kg/cm ²)	Air Cons. (cm ³ /time)	Air Inlet (Inch)	Hose Size (mm)	Packing
	GP-005A	20Ø x 126	0.081	S20	*	4-5	35	1/4"	5.0	28 pcs/0.6 cu-ft/G.W.: 5.83 kgs
	GP-005	30Ø x 120	0.134	S2	*	4-5	64	1/4"	5.0	28 pcs/0.6 cu-ft/G.W.: 6.95 kgs
	GP-010	36Ø x 136	0.189	S4	*	5-6	116	1/4"	6.5	28 pcs/0.6 cu-ft/G.W.: 9.89 kgs
	GP-020	45Ø x 170	0.344	S5	FD-6	5-6	230	1/4"	6.5	35 pcs/1.9 cu-ft/G.W.: 21.8 kgs
	GP-030	56Ø x 207	0.565	S8P	FD-8P	5-6	584	1/4"	8.0	35 pcs/1.9 cu-ft/G.W.: 36 kgs
	GP-040	56Ø x 300	0.897	S8P	FD-8P	5-6	956	1/4"	8.0	20 pcs/1.7 cu-ft/G.W.: 25 kgs

Blade Type	Capacity (mm)		Applied Model
	Copper Wire	Iron Wire	
S20	0.8	0.5	GP-005A
S2	1.0	0.5	GP-005
S4	1.6	1.0	GP-010
S5	2.6	2.0	GP-020
S8P	3.3	2.8	GP-030
	Stainless Steel Wire 2.0		
S8P	Plano Wire 1.2		GP-040
	4.8	4.0	
FD-6	Stainless Steel Wire 2.8		GP-020
	5.0 Soft Plastic	4.0 Hard Plastic	
FD-8P	10.0 Soft Plastic	6.5 Hard Plastic	GP-030
	13.0 Soft Plastic	6.5 Hard Plastic	GP-040

For Non-Insulated Terminal		
Blade Type	Capacity (mm)	Applied Model
A5P	1.25 sq	GP-020
A7P	1.25 sq, 2.0 sq, 5.5 sq	GP-030
A7WP-2	1.25-2.0 sq, 2.0-5.5 sq	GP-040
A7WP-3	1.25-2.0-5.5 sq	GP-040
A7P	8.0 sq	

For Insulated Terminal		
Blade Type	Capacity (mm)	Applied Model
AR7P	1.25 sq, 2.0 sq, 5.5 sq	GP-030
AR7WP	1.25-2.0 sq, 2.0-5.5 sq	GP-040
AR7P	8.0 sq	GP-040

AIR METAL SHEAR



Specifications	Capacity(mm)		Max Speed (rpm)	Net Weight (kgs)	Length (mm)	Air Cons. (m ³ /min)	Air Inlet (Inch)	Hose Size (mm)	Sound Pressure (dBA)	Vibration (m/sec ²)	Packing
	Steel	Aluminum									
	1.2	1.6	2,100	1.33	215	0.62	1/4"	6.5	85	4.0	10 pcs/0.9 cu-ft/G.W.: 13.9 kgs
	1.2	1.6	2,600	1.00	277	0.60	1/4"	6.5	82	< 2.5	12 pcs/1.0 cu-ft/G.W.: 16 kgs
	1.2	1.6	2,600	1.00	240	0.60	1/4"	6.5	82	< 2.5	12 pcs/1.1 cu-ft/G.W.: 16 kgs
	1.2	1.5	2,000	1.14	257	0.56	1/4"	6.5	82	3.9	20 pcs/1.16 cu-ft/G.W.: 24.2 kgs

AIR SOISSORS



Specifications	Capacity(mm)		Max Speed (rpm)	Net Weight (kgs)	Length (mm)	Air Cons. (m ³ /min)	Air Inlet (Inch)	Hose Size (mm)	Sound Pressure (dBA)	Vibration (m/sec ²)	Packing
	Steel	Aluminum									
	1.2	1.6	2,600	1.00	290	0.62	1/4"	6.5	82	< 2.5	12 pcs/1.1 cu-ft/G.W.: 16 kgs
	1.2	1.6	2,600	1.00	277	0.62	1/4"	6.5	82	< 2.5	12 pcs/1.1 cu-ft/G.W.: 16 kgs