

# AIR CAULKING GUN



GP-853



GP-853A  
GP-853AG  
GP-853BL



GP-853B



GP-853F



GP-853HR



GP-853HS  
GP-853H



GP-853M



GP-853MCL



GP-853D



GP-853DC



\* Sprayer & Caulker  
GP-853MSC

Recommended Air Pressure 30-60 psi (2.1-6.3 kgf/cm<sup>2</sup>)

Max. Air Pressure Releatable 160 psi  
For 8 oz Air Caulking Gun.

| Model     | Capacity Available (oz) |            | Specification   | Net Weight (kg) | Length (mm) | Packing                        |
|-----------|-------------------------|------------|---|-----------------|-------------|--------------------------------|
|           | Cartridge               | Sachet     |   |                 |             |                                |
| GP-853    | 9                       |            | • Steel Tube • No dropping  | 1.15            | 310         | 10 pcs/1.34 cu-ft/G.W.: 14 kgs |
| GP-853A   | 9,11,13                 |            | • w/Air Regulator • Pull Line   | 0.75            | 315         | 10 pcs/1.34 cu-ft/G.W.: 9 kgs  |
| GP-853AS  |                         | 9,11,13,15 | • w/Air Regulator • Pull Line   | 0.80            | 315         | 10 pcs/2.3 cu-ft/G.W.: 10 kgs  |
| GP-853BL  | 9,11,13                 | 9,11,13,15 | • w/Air Regulator • Pull Line   | 0.95            | 315         | 10 pcs/2.3 cu-ft/G.W.: 12 kgs  |
| GP-853B   | 9,11,13                 | 9,11,13,15 | • w/Air Regulator • Push Rod  | 0.95            | 315         | 10 pcs/2.3 cu-ft/G.W.: 12 kgs  |
| GP-853F   | 29                      |            | • For Construction • Pull Line  | 1.70            | 440         | 10 pcs/2.7 cu-ft/G.W.: 18 kgs  |
| GP-853HR  |                         | 9,11,13,15 | • Light in weight • Push Rod  | 1.00            | 325         | 10 pcs/2.4 cu-ft/G.W.: 12 kgs  |
| GP-853HS  |                         | 9,11,13,15 | • Light in weight • Pull Line   | 0.90            | 380         | 10 pcs/2.3 cu-ft/G.W.: 10 kgs  |
| GP-853H   | 9,11,13                 |            | • Light in weight • Pull Line   | 0.80            | 380         | 10 pcs/2.3 cu-ft/G.W.: 9 kgs   |
| GP-853M   | 9,11,13                 | 9,11,13,15 | • w/ Air Regulator • Push Rod   | 1.20            | 380         | 10 pcs/2.3 cu-ft/G.W.: 13 kgs  |
| GP-853MCL | 9,11,13                 | 9,11,13,15 | • w/ Air Regulator & Auto Air Exhaust • Pull Line   | 0.90            | 380         | 10 pcs/2.4 cu-ft/G.W.: 13 kgs  |
| GP-853D   | 9,11,13                 | 9,11,13,15 | • w/Spray Nozzle, Fluid Valve & Air Regulator • For Polyurethane and Silicone • Push Rod                    | 1.20            | 375         | 10 pcs/2.4 cu-ft/G.W.: 13 kgs  |
| GP-853DC  | 9,11,13                 | 9,11,13,15 | • w/Spray Nozzle, Fluid Valve & Auto Air Exhaust • For Polyurethane and Silicone • Push Rod • Pin Regulator | 1.20            | 375         | 10 pcs/2.4 cu-ft/G.W.: 13 kgs  |
| GP-853MSC | 9,11,13,15              |            | • w/Fluid Nozzle & Auto Air Exhaust • For Carpenter & Construction, Glass • Pull Line                       | 1.20            | 370         | 10 pcs/2.4 cu-ft/G.W.: 13 kgs  |

**\* Features:**

- Filter element: 5µ
- Adj. pressure range: 0.5-8.5 kgf/cm<sup>2</sup>
- Max. service pressure: 9.9 kgf/cm<sup>2</sup>

**\* Operating temp. range: 5-60°C**

- Drain capacity: 80 ml
- Oil capacity: 125 ml
- Recommend lubricant: ISO VG-32

# PREPARATION UNIT-F.R.L.



GP-815H  
GP-816H  
GP-817H



GP-818H  
GP-819H



GP-815HI  
GP-816HI  
GP-817HI



GP-814S  
GP-815S

| Model    | Port Size (inch) pt / npt | Max Flow (m <sup>3</sup> /min) | Construction unit |           |            | Packing                       |
|----------|---------------------------|--------------------------------|-------------------|-----------|------------|-------------------------------|
|          |                           |                                | Filter            | Regulator | Lubricator |                               |
| GP-815H  | 1/4"                      | 1.75                           | GP-815HA          | GP-815HB  | GP-815HC   | 10 pcs/2.2 cu-ft/G.W.: 22 kgs |
| GP-816H  | 3/8"                      | 2.50                           | GP-816HA          | GP-816HB  | GP-816HC   | 10 pcs/2.2 cu-ft/G.W.: 22 kgs |
| GP-817H  | 1/2"                      | 3.00                           | GP-817HA          | GP-817HB  | GP-817HC   | 10 pcs/2.2 cu-ft/G.W.: 22 kgs |
| GP-818H  | 3/4"                      | 4.60                           | GP-818HA          | GP-818HB  | GP-818HC   | 6 pcs/2.48 cu-ft/G.W.: 27 kgs |
| GP-819H  | 1"                        | 5.20                           | GP-819HA          | GP-819HB  | GP-819HC   | 6 pcs/2.48 cu-ft/G.W.: 27 kgs |
| GP-815HI | 1/4"                      | 1.75                           | GP-815HAB         |           |            | 12 pcs/1.7 cu-ft/G.W.: 20 kgs |
| GP-816HI | 3/8"                      | 2.50                           | GP-816HAB         |           |            | 12 pcs/1.7 cu-ft/G.W.: 20 kgs |
| GP-817HI | 1/2"                      | 3.00                           | GP-817HAB         |           |            | 12 pcs/1.7 cu-ft/G.W.: 20 kgs |
| GP-814S  | 1/8"                      | 1.00                           | GP-814SAB         |           |            | 30 pcs/1.3 cu-ft/G.W.: 20 kgs |
| GP-815S  | 1/4"                      | 1.10                           | GP-815SAB         |           |            | 30 pcs/1.3 cu-ft/G.W.: 20 kgs |