

SPRING BALANCER



- ※ Features
 - Keeps working bench in good order.
 - Increases working efficiency.
 - Helps operator feel less tired and increase safety.
- ※ Convenient force adjustment by rotary adjustment cap.

- ※ Special design.
 - Increasing screw diameter is balanced by increasing spring force so that the output force is balanced and the tool stops at wherever it is pulled.

Specifications

Model No.	Capacity (kg)	Travel (ft)	Wire Dia. (mm)	Net Weight (kgs)	Packing
GP-SB01A	0.6 - 1.5	1.6	2.5	0.52	40 pcs/1.7 cu-ft/G.W.: 21.0 kgs
GP-SB01B	1.0 - 2.0	1.6	2.5	0.53	40 pcs/1.7 cu-ft/G.W.: 21.0 kgs
GP-SB01C	1.5 - 3.0	1.3	2.5	0.54	40 pcs/1.6 cu-ft/G.W.: 22.7 kgs
GP-SB01F	3.0 - 5.0	1.5	3.2	0.81	30 pcs/1.6 cu-ft/G.W.: 24.1 kgs
GP-SB01J	0.3 - 1.2	1.6	4.0	0.57	30 pcs/1.6 cu-ft/G.W.: 18.7 kgs
GP-SB01K	0.8 - 2.0	1.6	4.0	0.57	30 pcs/1.6 cu-ft/G.W.: 20.1 kgs
GP-SB01I	9.0 - 15.0	1.3	4.7	3.61	4 pcs/1.9 cu-ft/G.W.: 15.44 kgs
GP-SB02I	5.0 - 9.0	1.3	4.7	3.59	4 pcs/1.9 cu-ft/G.W.: 14.9 kgs
GP-SB01GR	5.0 - 7.0	1.3	3.2	1.85	10 pcs/1.7 cu-ft/G.W.: 20.9 kgs
GP-SB03I	3.0 - 5.0	1.3	3.2	1.82	10 pcs/1.7 cu-ft/G.W.: 19.2 kgs
GP-SB04I	1.5 - 3.0	1.3	3.2	1.73	10 pcs/1.7 cu-ft/G.W.: 18.3 kgs
GP-SB05I	0.5 - 1.5	1.3	2.0	0.73	20 pcs/1.9 cu-ft/G.W.: 15.6 kgs
GP-SB06I	15 - 22	1.5	4.8	7.10	1 pc/0.6 cu-ft/G.W.: 7.7 kgs
GP-SB07I	22 - 30	1.5	4.8	7.60	1 pc/0.6 cu-ft/G.W.: 8.3 kgs



AIR HOSE BALANCER



Specifications

Model No.	Capacity (kg)	Hose Size (mm)	Hose Length (ft)	Inlet (inch)	Net Weight (kgs)	Case Size (mm)	Working Pressure (kg/cm ²)	Break Pressure (kg/cm ²)	Packing
GP-AB02A	0.5 - 1.5	6.5 x 10	1.4	1/4"	1.80	277 X 264 X 109	100 (7)	400 (28)	6 pcs/1.9 cu-ft/G.W.: 11.7 kgs
GP-AB02B	1.5 - 3.0	6.5 x 10	1.4	1/4"	1.90	277 X 264 X 109	100 (7)	400 (28)	6 pcs/1.9 cu-ft/G.W.: 12.4 kgs
GP-AB02C	3.0 - 5.0	6.5 x 10	1.4	1/4"	2.00	277 X 264 X 109	100 (7)	400 (28)	6 pcs/1.9 cu-ft/G.W.: 13.0 kgs
GP-RB02	0.6 - 1.5	5 x 8	1.2	1/4"	0.86	205 X 155 X 105	100 (7)	400 (28)	10 pcs/1.4 cu-ft/G.W.: 11 kgs
GP-RB02B	0.6 - 1.5	5 x 8	2.0	1/4"	0.90	205 X 155 X 105	100 (7)	400 (28)	10 pcs/1.4 cu-ft/G.W.: 11 kgs

Hose Material : Polyurethane

AIR HOSE REEL



Specifications

Model No.	Hose Size (mm)	Hose Length (ft)	Inlet (inch)	Net Weight (kgs)	Case Size (mm)	Working Pressure (kg/cm ²)	Break Pressure (kg/cm ²)	Packing
GP-RB01A	5 x 8	7.5	1/4"	1.4	240 x 215 x 95	100 (7)	350 (24)	10 pcs/2.0 cu-ft/G.W.: 20 kgs
GP-RB01B	6.5 x 9.5	6.0	1/4"	1.4	240 x 215 x 95	100 (7)	350 (24)	10 pcs/2.0 cu-ft/G.W.: 20 kgs
GP-RB05A	6.5 x 10	8	1/4"	2.8	345 x 300 x 145	200 (14)	800 (55)	6 pcs/4.2 cu-ft/G:22 kgs
GP-RB05B	6.5 x 10	10	1/4"	2.9	345 x 300 x 145	200 (14)	800 (55)	6 pcs/4.2 cu-ft/G:22 kgs
GP-RB05C	6.5 x 10	12	1/4"	3.0	345 x 300 x 145	200 (14)	800 (55)	6 pcs/4.2 cu-ft/G:22 kgs
GP-RB05D	8 x 12	8	1/4"	2.9	345 x 300 x 145	200 (14)	800 (55)	6 pcs/4.2 cu-ft/G:22 kgs
GP-RB03A	6.5 x 10	30	1/4"	7.5	350 x 290 x 390	220 (15)	870 (60)	2 pcs/2.9 cu-ft/G.W.: 17 kgs
GP-RB03B	6.5 x 10	50	1/4"	9.0	350 x 290 x 390	220 (15)	870 (60)	2 pcs/2.9 cu-ft/G.W.: 20 kgs
GP-RB03C	8.5 x 12.5	30	1/4"	8.0	350 x 290 x 390	220 (15)	870 (60)	2 pcs/2.9 cu-ft/G.W.: 17 kgs
GP-RB03D	8.5 x 12.5	40	1/4"	9.0	350 x 290 x 390	220 (15)	870 (60)	2 pcs/2.9 cu-ft/G.W.: 18 kgs

Hose Material : Polyurethane Braid

- ※ Features
 - PU braid hose carries long duration and cold resistance yet light weight.
 - Excellent flexibility resists pressure from passing cars while working on the road.
 - 360° swivel base and long hose allow operation in wide range.