

## AIR STRAIGHT DRILL



GP-330



GP-340



GP-350



GP-330T



GP-330ST



GP-330STN



GP-330A

Specifications								Recommended Air Pressure 90 psi (6.3 kg/cm <sup>2</sup> )		
Model	Capacity (Inch)	Max. Speed (rpm)	Net Weight (kg)	Length (mm)	Air Cons. (m <sup>3</sup> /min)	Air Inlet (Inch)	Hose Size (mm)	Sound Pressure (dBA)	Vibration (m/sec <sup>2</sup> )	Packing
GP-330	3/8"	2,500	1.00	225	0.62	1/4"	6.5	95	< 2.5	20 pcs/1.29 cu-ft/G.W.: 21 kgs
GP-340	3/8"	22,000	0.92	205	0.51	1/4"	6.5	94	< 2.5	20 pcs/1.0 cu-ft/G.W.: 19 kgs
GP-350	3/8"	1,600	0.87	225	0.23	1/4"	6.5	75	< 2.5	20 pcs/1.1 cu-ft/G.W.: 18 kgs
GP-330T	3/8"	2,000	0.97	228	0.63	1/4"	6.5	85	< 2.5	20 pcs/0.93 cu-ft/G.W.: 20.5 kgs
GP-330ST	3/8"	2,600	1.08	218	0.61	1/4"	6.5	82	< 2.5	12 pcs/1.10 cu-ft/G.W.: 14 kgs
GP-330STN	3/8"	3,600	1.08	218	0.64	1/4"	6.5	82	< 2.5	12 pcs/1.10 cu-ft/G.W.: 14 kgs
GP-330A	1/4"	6,500	0.62	175	0.45	1/4"	6.5	85	< 2.5	20 pcs/0.5 cu-ft/G.W.: 15 kgs

## AIR ANGLE DRILL



GP-835TB



GP-835ADS



GP-835C



GP-835F



GP-836C

Specifications								Recommended Air Pressure 90 psi (6.3 kg/cm <sup>2</sup> )		
Model	Capacity (Inch)	Max. Speed (rpm)	Net Weight (kg)	Length (mm)	Air Cons. (m <sup>3</sup> /min)	Air Inlet (Inch)	Hose Size (mm)	Sound Pressure (dBA)	Vibration (m/sec <sup>2</sup> )	Packing
GP-835TB	3/8"	1,900	0.96	220	0.39	1/4"	6.5	92	< 2.5	20 pcs/1.40 cu-ft/G.W.: 21 kgs
GP-835ADS	3/8"	2,200	1.17	200	0.63	1/4"	6.5	82	< 2.5	12 pcs/0.8 cu-ft/G.W.: 15 kgs
GP-835C	3/8"	2,400	1.10	170	0.31	1/4"	6.5	82	< 2.5	10 pcs/0.73 cu-ft/G.W.: 12 kgs
GP-835F	3/8"	2,200	1.20	172	0.52	1/4"	6.5	83	< 2.5	10 pcs/1.73 cu-ft/G.W.: 13 kgs
GP-836C	1/2"	800	1.45	203	0.70	1/4"	6.5	90	< 2.5	10 pcs/0.92 cu-ft/G.W.: 18 kgs

# AIR REVERSIBLE ANGLE DRILL



GP-836D



GP-840A



GP-840S



GP-26D



Reversible Type  
Keyless Chuck  
GP-840B



Keyless Chuck  
GP-840C



GP-840SK

GP-840SK Air Reversible Angle Drill Kit	
1 pc	Air Reversible Angle Drill (GP-840S)
13 pcs	Drill Bits
1 pc	Nipple
1 pc	Chuck Key
1 pc	Oil Pot
1 pc	Plastic Box
Packing	5 sets/0.98 cu-ft/G.W.: 10 kgs

Specifications		Recommended Air Pressure 90 psi (6.3 kg/cm <sup>2</sup> )								
Model	Capacity (Inch)	Max. Speed (rpm)	Net Weight (kgs)	Length (mm)	Air Cons. (m <sup>3</sup> /min)	Air Inlet (Inch)	Hose Size (mm)	Sound Pressure (dBA)	Vibration (m/sec <sup>2</sup> )	Packing
GP-836D	1/2"	800	1.45	230	0.70	1/4"	6.5	82	< 2.5	10 pcs/0.92 cu-ft/G.W.: 18 kgs
GP-840A	3/8"	2,300	1.30	191	0.56	1/4"	6.5	83	< 2.5	10 pcs/0.73 cu-ft/G.W.: 15 kgs
GP-840S	3/8"	1,800	1.20	177	0.56	1/4"	6.5	87	< 2.5	10 pcs/1.73 cu-ft/G.W.: 13 kgs
GP-26D	5/8"	1,000	6.40	370	0.80	1/4"	6.5	87	< 2.5	2 pcs/0.75 cu-ft/G.W.: 15 kgs

# HEAVY DUTY AIR ANGLE DRILL



GP-835G  
GP-835GR Reversible Type



GP-836G  
GP-836GR Reversible Type



Keyless Chuck  
GP-835B



Keyless Chuck  
GP-836B3, B5, B8



Reversible Type  
Keyless Chuck  
GP-836E2, E4, E8

Specifications		Recommended Air Pressure 90 psi (6.3 kg/cm <sup>2</sup> )								
Model	Capacity (Inch)	Max. Speed (rpm)	Net Weight (kgs)	Length (mm)	Air Cons. (m <sup>3</sup> /min)	Air Inlet (Inch)	Hose Size (mm)	Sound Pressure (dBA)	Vibration (m/sec <sup>2</sup> )	Packing
GP-840B	3/8"	1,800	1.10	198	0.62	1/4"	10	90	< 2.5	10 pcs/0.85 cu-ft/G.W.: 14 kgs
GP-840C	3/8"	2,200	1.08	194	0.62	1/4"	10	88	< 2.5	10 pcs/0.82 cu-ft/G.W.: 12 kgs
GP-835B	3/8"	3,500	1.12	165	0.53	1/4"	10	75	< 2.5	10 pcs/0.82 cu-ft/G.W.: 15.2 kgs
GP-836A3	1/2"	300	1.50	228	0.50	1/4"	10	90	< 2.5	10 pcs/0.8 cu-ft/G.W.: 14 kgs
GP-836B5	1/2"	500	1.50	228	0.50	1/4"	10	90	< 2.5	10 pcs/0.8 cu-ft/G.W.: 14 kgs
GP-836B8	1/2"	850	1.50	228	0.50	1/4"	10	90	< 2.5	10 pcs/0.8 cu-ft/G.W.: 14 kgs
GP-836E2	1/2"	250	1.50	229	0.70	1/4"	10	90	< 2.5	10 pcs/0.82 cu-ft/G.W.: 14 kgs
GP-836E4	1/2"	450	1.50	229	0.70	1/4"	10	90	< 2.5	10 pcs/0.82 cu-ft/G.W.: 14 kgs
GP-836E8	1/2"	800	1.50	229	0.70	1/4"	10	90	< 2.5	10 pcs/0.82 cu-ft/G.W.: 14 kgs
GP-835G	3/8"	2,000	1.25	181	0.79	1/4"	6.5	91	< 2.5	10 pcs/0.98 cu-ft/G.W.: 15 kgs
GP-835GR	3/8"	2,000	1.25	181	0.79	1/4"	6.5	91	< 2.5	10 pcs/0.98 cu-ft/G.W.: 15 kgs
GP-836G	1/2"	460	1.77	220	0.79	1/4"	6.5	92	< 2.5	10 pcs/0.98 cu-ft/G.W.: 20 kgs
GP-836GR	1/2"	460	1.77	220	0.79	1/4"	6.5	92	< 2.5	10 pcs/0.98 cu-ft/G.W.: 20 kgs