

AIR SCREW DRIVER (IMPACT TYPE)



Specifications											Recommended Air Pressure 90 psi (6.3 kg/cm ²)	
Model	Capacity (mm)	Shank Size	Free Speed (rpm)	Max. Torque ft.Lb(Nm)	Net Weight (kgs)	Length (mm)	Air Cons. (m ³ /min)	Air Inlet (inch)	Hose Size (mm)	Sound Pressure (dBA)	Vibration (m/sec ²)	Packing
GP-866	4.0 - 5.0	1/4"	8,000	26 (35)	0.68	190	0.31	1/4"	6.5	86	< 2.5	20 pcs/0.70 cu-ft/G.W.: 15.5 kgs
GP-866Q	3.5 - 4.5	1/4"	8,000	20 (27)	0.68	190	0.31	1/4"	6.5	86	< 2.5	20 pcs/0.73 cu-ft/G.W.: 16 kgs
GP-867	5.0 - 6.0	1/4"	8,500	17.4 (23.5)	1.12	215	0.49	1/4"	6.5	95	< 2.5	20 pcs/1.44 cu-ft/G.W.: 24.5 kgs
GP-867D	5.0 - 6.0	1/4"	6,500	36 (48)	1.10	210	0.49	1/4"	6.5	92	< 2.5	20 pcs/1.50 cu-ft/G.W.: 23 kgs
GP-868	6.0 - 8.0	1/4"	7,000	148 (200)	1.20	210	0.36	1/4"	6.5	89	< 2.5	20 pcs/1.10 cu-ft/G.W.: 25 kgs
GP-869	6.0 - 8.0	1/4"	12,000	74 (100)	0.95	195	0.36	1/4"	6.5	92	< 2.5	20 pcs/1.10 cu-ft/G.W.: 21 kgs

AIR SCREW DRIVER (SLIP-CLUTCH TYPE)



Specifications											Recommended Air Pressure 90 psi (6.3 kg/cm ²)	
Model	Capacity (mm)	Shank Size	Free Speed (rpm)	Max. Torque ft.Lb(Nm)	Net Weight (kgs)	Length (mm)	Air Cons. (m ³ /min)	Air Inlet (inch)	Hose Size (mm)	Sound Pressure (dBA)	Vibration (m/sec ²)	Packing
GP-802	5.0 - 6.0	1/4"	1,800	3.0 (4)	0.65	210	0.35	1/4"	5.0	84	< 2.5	20 pcs/1.10 cu-ft/G.W.: 14 kgs
GP-804HP	2.2 - 3.0	1/4"	1,500	1.5 (2)	0.78	210	0.35	1/4"	5.0	78	< 2.5	20 pcs/1.10 cu-ft/G.W.: 17 kgs
GP-861H	3.0 - 4.0	1/4"	1,500	2.2 (3)	0.65	228	0.21	1/4"	5.0	83	< 2.5	20 pcs/1.10 cu-ft/G.W.: 14 kgs
GP-861H1	3.0 - 4.0	1/4"	600	5.9 (8)	0.90	228	0.35	1/4"	5.0	83	< 2.5	20 pcs/1.40 cu-ft/G.W.: 19 kgs
GP-865M	6.0	1/4"	1,700	9.6(13)	1.16	265	0.48	1/4"	5.0	86	< 2.5	10 pcs/0.60 cu-ft/G.W.: 14 kgs

AIR SCREW DRIVER (SHUT-OFF TYPE)



- Push Start
 - Auto Shut off
 - Rear Exhaust
- GP-861C**
GP-904C
GP-905C
GP-905D



- Push Start
 - Auto Shut off
 - Rear Exhaust
- GP-906A**



- Push Start
 - Auto Shut off
 - Rear Exhaust
- GP-906B**

Specifications

Recommended Air Pressure 90 psi (6.3 kg/cm²)

Model	Capacity (mm)	Shank Size	Free Speed (rpm)	Max. Torque (Nm)	Net Weight (kgs)	Length (mm)	Air Cons. (m ³ /min)	Air Inlet (inch)	Hose Size (mm)	Sound Pressure (dBA)	Vibration (m/sec ²)	Packing
GP-861C	3.0 - 4.0	1/4"	1,000	0.39-0.78	0.70	230	0.28	1/4"	5.0	86	< 2.5	20 pcs/1.10 cu-ft/G.W.: 16 kgs
GP-904C	3.5	1/4"	1,000	1.2-2.2	0.71	229	0.28	1/4"	5.0	75	< 2.5	20 pcs/1.40 cu-ft/G.W.: 14.5 kgs
GP-905C	4.0 - 5.0	1/4"	950	2.0-4.8	0.93	250	0.28	1/4"	5.0	80	< 2.5	20 pcs/2.00 cu-ft/G.W.: 26.3 kgs
GP-905D	5.0 - 6.0	1/4"	650	3.0-7.0	0.93	250	0.28	1/4"	5.0	80	< 2.5	20 pcs/2.00 cu-ft/G.W.: 26.3 kgs
GP-906A	2	3.5 mm	2,000	0.25-0.35	0.35	190	0.07	1/4"	5.0	40	< 2.5	10 pcs/0.90 cu-ft/G.W.: 5 kgs
GP-906B	3	3.5 mm	800	0.35-1.0	0.37	190	0.07	1/4"	5.0	40	< 2.5	10 pcs/0.90 cu-ft/G.W.: 5 kgs

AIR ANGLE SCREW DRIVER (IMPACT TYPE)



GP-801LA

GP-950



GP-951

Specifications

Recommended Air Pressure 90 psi (6.3 kg/cm²)

Model	Capacity (mm)	Shank Size	Free Speed (rpm)	Max. Torque ft.-lb/(Nm)	Net Weight (kgs)	Length (mm)	Air Cons. (m ³ /min)	Air Inlet (inch)	Hose Size (mm)	Sound Pressure (dBA)	Vibration (m/sec ²)	Packing
GP-801LA	5.0 - 6.0	1/4"	10,000	26 (35)	0.88	140	0.42	1/4"	6.5	90	< 2.5	15 pcs/1.30 cu-ft/G.W.: 16 kgs
GP-950	6.0 - 8.0	1/4"	10,000	135 (183)	0.95	135	0.42	1/4"	6.5	88	< 2.5	20 pcs/1.70 cu-ft/G.W.: 21 kgs
GP-951	6.0 - 8.0	1/4"	8,500	44.5 (60)	1.15	176	0.48	1/4"	6.5	87	< 2.5	10 pcs/1.20 cu-ft/G.W.: 14.5 kgs

**AIR ANGLE
SCREW
DRIVER
(SLIP-CLUTCH
TYPE)**



Side Exhaust
GP-802L90



Rear Exhaust
GP-804L90



GP-861J



GP-861J1



GP-862H



GP-862H1

Specifications

Recommended Air Pressure 90 psi (6.3 kg/cm²)

Model	Capacity (mm)	Shank Size	Free Speed (rpm)	Max Torque ft.-lb/(Nm)	Net Weight (kgs)	Length (mm)	Air Cons. (m ³ /min)	Air Inlet (inch)	Hose Size (mm)	Sound Pressure (dBA)	Vibration (m/sec ²)	Packing
GP-802L90	5.0 - 6.0	1/4"	1,600	3.0 (4)	0.90	230	0.28	1/4"	5.0	80	< 2.5	20 pcs/1.40 cu-ft/G.W.: 19 kgs
GP-804L90	3.0 - 4.0	1/4"	1,400	2.2 (3)	0.90	230	0.28	1/4"	5.0	80	< 2.5	20 pcs/1.40 cu-ft/G.W.: 19 kgs
GP-861J	6	1/4"	1,800	6.6 (9)	1.40	210	0.73	1/4"	5.0	92	< 2.5	10 pcs/0.92 cu-ft/G.W.: 15 kgs
GP-861J1	8	1/4"	800	9.5 (13)	1.50	230	0.73	1/4"	5.0	92	< 2.5	10 pcs/0.92 cu-ft/G.W.: 15 kgs
GP-862H	5.0 - 6.0	1/4"	1,800	6.6 (9)	1.20	210	0.63	1/4"	5.0	98	< 2.5	10 pcs/0.91 cu-ft/G.W.: 14 kgs
GP-862H1	5.0 - 6.0	1/4"	800	9.5 (13)	1.25	230	0.56	1/4"	5.0	88	< 2.5	10 pcs/0.91 cu-ft/G.W.: 15 kgs

**AIR
SCREW
DRIVER
KITS**



GP-861JK, GP-861J1K



GP-862HK, GP-862H1K

GP-861JK or GP-861J1K		GP-862HK or GP-862H1K	
1 pc	Air Screw Driver (GP-861JK or GP861J1K)	1 pc	Air Screw Driver (GP-862HK or GP-862H1K)
7 pcs	Screw Bits	7 pcs	Screw Bits
2 pcs	Cap Spanner	2 pcs	Cap Spanner
1 pc	Plastic Box	1 pc	Plastic Box
Packing 5 sets/0.98 cu-ft/G.W.: 10 kgs		Packing 5 sets/0.98 cu-ft/G.W.: 10 kgs	