

AIR
C HOG
RING
PILER /
NAILER



Closure Dia.

- 8.0 GP-AC01-80
- 6.5 GP-AC01-65
- 5.5 GP-AC01-55
- 4.5 GP-AC01-45
- 8.0 GP-AC03-80

Specifications Recommended Air Pressure 90 ~ 105 psi

Model	Gauge	Wire Dia. (mm)	Crown (mm)	Shank Height (mm)	Closure Dia. (mm)	Load Capacity (pcs)	Net Weight (kgs)	Tool Size (LxHxW)	Packing
GP-AC01-80	15	1.8	23.7	12	8.0	100	1.45	315 x 182 x 90	6 pcs/2 cu-ft/12 kgs
GP-AC01-65	15	1.8	23.7	12	6.5	100	1.45	315 x 182 x 90	6 pcs/2 cu-ft/12 kgs
GP-AC01-55	15	1.8	23.7	12	5.5	100	1.45	315 x 182 x 90	6 pcs/2 cu-ft/12 kgs
GP-AC01-45	15	1.8	23.7	12	4.5	100	1.45	315 x 182 x 90	6 pcs/2 cu-ft/12 kgs
GP-AC03-80	15	1.8	23.7	12	8.0	100	1.50	332 x 182 x 90	6 pcs/2 cu-ft/13 kgs

AIR
GREASE
GUN



Specifications Recommended Air Pressure 60 ~ 90 psi

Model	Capacity Bulk (cc)	Capacity Cartridge (oz)	Net Weight (kgs)	Air Inlet (inch)	Packing
GP-850N	400	14	1.15	1/4"	10 pcs/1.53 cu-ft/G.W.: 16 kgs
GP-850C	400	14	1.55	1/4"	10 pcs/1.8 cu-ft/G.W.: 18.3 kgs
GP-850CR	400	14	1.67	1/4"	10 pcs/1.9 cu-ft/G.W.: 18 kgs
GP-850KA	450	14	1.00	1/4"	10 pcs/2.5 cu-ft/G.W.: 14 kgs
GP-850KB	450	14	1.00	1/4"	10 pcs/2.5 cu-ft/G.W.: 14 kgs